

What is claimed is:

1. A liner for a hydrothermal pressure vessel, said vessel having a wall defining a chamber and said liner comprising:

a porous layer positioned in said chamber of said vessel;

5 a non-porous layer positioned against said porous layer with said porous layer between said non-porous layer and said wall of said vessel;

a seal for coupling said non-porous layer to said wall to encapsulate said porous layer therebetween; and

10 means for establishing fluid communication with said porous material.

2. A liner as recited in claim 1 further comprising at least one connector extending through said wall and into contact with said porous layer for conveying operational information from said porous layer.

15 3. A liner as recited in claim 2 further comprising a pressure sensor for determining the pressure in said porous layer.

4. A liner as recited in claim 2 further comprising a chemical species sensor for determining the presence of a chemical species in said porous layer.

20 5. A liner as recited in claim 2 further comprising a flow sensor for determining the flow in said porous layer.

6. A liner as recited in claim 1 further comprising at least one partition positioned between said non-porous layer and said wall for dividing said porous layer into sections and for isolating said sections from each other.

7. A liner as recited in claim 1 wherein said porous layer is positioned adjacent said wall of said vessel.

8. A liner as recited in claim 1 further comprising an insulation layer positioned adjacent said wall of said vessel between said porous layer and  
5 said wall of said vessel.

9. A liner as recited in claim 1 wherein said means in fluid communication with said porous layer for pumping a heat transfer fluid therethrough comprises a first connector for allowing said heat transfer fluid to flow into said porous layer, a second connector for allowing said heat transfer  
10 fluid to flow out of said porous layer and a pump in fluid communication with said first connector.

10. A liner as recited in claim 1 further comprising a sensor for performing leak detection measurements, said sensor embedded in said porous layer for passing a signal through said wall.

11. A liner for a hydrothermal pressure vessel, said vessel having a wall defining a chamber and said liner comprising:

a porous layer positioned in said chamber of said vessel;

5 a non-porous layer positioned against said porous layer with said porous layer between said non-porous layer and said wall of said vessel;

a seal for coupling said non-porous layer to said wall to encapsulate said porous layer therebetween;

10 a partition positioned between said non-porous layer and said wall for dividing said porous layer into a first section and a second section and for isolating said sections from each other;

means in fluid communication with said first section of said porous layer for selectively pumping a heat transfer fluid therethrough; and

15 means for establishing fluid communication with said second section of said porous layer.

12. A liner as recited in claim 11 further comprising a first connector extending through said wall and into contact with said first section of said porous layer for conveying operational information from said first section of said porous layer and a second connector extending through said wall and into contact with said second section of said porous layer for conveying operational information from said second section of said porous layer.

20

13. A method for hydrothermal treatment of a reactant comprising the steps of:

5 providing a vessel, said vessel having a wall and defining a chamber, said wall having a liner formed with a porous layer and a non-porous layer, said non-porous layer sealed to said wall to encapsulate said porous layer therebetween;

introducing the reactant, an oxidizer and water into said chamber;

10 converting said reactant into reaction products by combining said reactant said oxidizer and said water together in said chamber; and

pumping a heat transfer fluid through said porous material to maintain a pre-selected temperature for the liner.

15 14. A method as recited in claim 13 wherein said pumping step is performed before said converting step to pre-heat said chamber.

15. A method as recited in claim 13 wherein said pumping step is performed during said converting step to cool said reactor vessel.

20 16. A method as recited in claim 13 wherein said pumping step is performed during said converting step to cool said non-porous layer of said liner.

17. A method as recited in claim 13 wherein said pumping step is performed during said converting step to recover heat generated from said converting step.

18. A method as recited in claim 13 wherein said pumping step is performed after said converting step to cool said liner to remove said liner from said vessel.

19. A method as recited in claim 13 wherein said converting step  
5 occurs at a temperature of at least 374 degrees Celsius and a pressure of at least 25 bar.

20. A method as recited in claim 13 wherein said converting step occurs at a temperature of at least 374 degrees Celsius and a pressure of at least 220 bar.